

ULFX6000 range - UL intelligent addressable control panels



The Eaton ULFX6000 is a high specification intelligent addressable, wall or rack mounted, UL Listed control panel available in various loop configurations. It combines sophisticated functionality with simple operation and aesthetically pleasing design.

The control panel has the ability to support complex cause and effect programming (via site installer) and a wide range of user controllable functions that make the panel ideal for a diverse range of projects from industrial applications through to large multi site commercial developments.

The ULFX6000 uses soft addressing to minimise installation time and remove the potential for error associated with manual addressing. It can operate as a stand alone panel or as part of a networked system, and has powerful programming options that allow configurable control over whether messages from specific panels are transmitted around the network or remain local.

Features and benefits

- Large versatile touch-screen user interface
- 2 or 4 Class A Style 7 SLC loops
- Event history buffer (9,999 events) with date/time stamp
- 4 Notification appliance circuit (NAC's) outputs
- Dedicated alarm, trouble, AC trouble relays
- Integral short circuit isolators
- Up to 200 addresses per loop
- Full network capability up to 126 panels
- Supports a comprehensive range of soft addressing modules and devices for greater flexibility in design
- Menu driven graphical user interface for ease of operation
- Reduced commissioning time through soft addressing and auto learn functions
- Programming and trouble shooting time minimised by using a range of features such as auto config, walk test, system details menus


UL Addressable fire products

ULFX6000 range

Technical specification


Code	ULFX6000 / ULFX6000RM
Description	UL intelligent addressable control panel
Standards	UL864 9th edition
Primary operating supply	120V ac / 240V ac, 60Hz, 2.0A supervised
Secondary operating supply	
Battery voltage	24V dc
Battery charge current	1.0A (max)
Battery derating factor	0.1
Battery capacity supervised	12Ah (max)
Notification appliance circuits Class B, Style Y, Sounder Group 1, Sounder 1, Sounder Group 1, Sounder 2, Sounder Group 2	
Output voltage	24V dc
Output current	0.75A (max)
Line impedance	50Ω When powered by 240V ac, the maximum current of 3.0A is shared between these circuits When powered by 120V ac, the maximum current of 2.25A is shared between these circuits Circuits are supervised, power limited and regulated.
Notification appliance circuits Class B, Style Y, SYNC MODULE. NAC1, NAC2	
Output voltage	24V dc
Output current	0.5A (max)
Line impedance	50Ω (max) The maximum current of 0.5A is shared between these circuits Circuits are supervised, power limited and regulated.
Alarm, trouble contacts. Relay expansion	
Unity power factor	30V dc For connection to power limited sources only
Aux relay (AC Trouble) contacts	
Unity power factor	30V dc, 1A For connection to power limited sources only
Signaling line circuit Style [7] Class [A] – (Addressable Loop)	
Rated voltage	24V dc
Maximum current	500mA
Line impedance	50Ω (max) Supervised, power limited
Network SLC	
Voltage	5V dc
Current	100mA (max)
Line impedance	50Ω (max) Power limited Limited to same enclosure installations
Physical	
IP Rating	IP30
Compatibility	
Suitable for use with	Eaton UL fire systems

Dimensions



Description	H (mm)	W (mm)	D1 (mm)	D2 (mm)
ULFX6000	397	497	75	130
ULFX6000RM	398	505	48	118

System block diagram



Catalogue numbers

Description	Code
2 loop panel	ULFX60002G
4 loop panel	ULFX60004G
2 loop panel, integral printer	ULFX60002GP
4 loop panel, integral printer	ULFX60004GP
2 loop panel, network card	ULFX60002GNC
4 loop panel, network card	ULFX60004GNC
2 loop panel, integral printer, network card	ULFX60002GPNC
4 loop panel, integral printer, network card	ULFX60004GPNC
2 loop panel, network card, red metal box	ULFX60002NCRM
4 loop panel, network card, red metal box	ULFX60004NCRM
Rack mounted 2 loop panel	ULFXR6000L2
Rack mounted 4 loop panel	ULFXR6000L4
Rack mounted 2 loop panel c/w network card	ULFXR6000L2NC
Rack mounted 4 loop panel c/w network card	ULFXR6000L4NC
Loop connected repeater panel	ULFX6000PR
Touchscreen network repeater panel	ULFPTR6000

Eaton Electrical Systems Ltd
Wheatley Hall Road
Doncaster
South Yorkshire
DN2 4NB
UK
Eaton.com

© 2020 Eaton
All Rights Reserved
Publication No.TD-EN-450-310718/CSSC-1499
June 2020

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Powering Business Worldwide